AMENDMENT AND RESPONSE UNDER 37 CFR § 1.111

Serial Number: 09/186,817

Filing Date: November 5, 1998

Title: MULTIPLE AUDIO DACs WITH PC COMPATIBILITY

Page 2 Dkt: 450.183US1

## In the Claims

The pending claims are set forth as follows:

- 1. (Original) A personal computer system comprising:
  - a plurality of audio digital-to-analog converters; and
- a controller configured to receive digital audio signals from multiple sources and route the digital audio signals to a selected digital-to-analog converter based on a desired converter quality.
- 2. (Original) A personal computer system comprising:
  - one or more standard digital audio sources;
  - one or more high quality digital audio sources;
- means for routing digital audio signals from standard digital audio sources to a standard quality digital-to-analog converter; and
- means for routing digital audio signals from a high-quality digital audio source to a high quality digital-to-analog converter.
- 3. (Original) The personal computer system of claim 2 where any of the high quality or standard quality digital-to-analog converters are coder-decoders (CODECs) that contain both digital-to-analog converters and analog-to-digital converters.
- 4. (Original) The personal computer system of claim 1 where a user configures the controller such that the controller assigns a digital-to analog converter and a priority to each of the plurality of audio sources, and the controller routes the digital audio signal with the highest priority for each of the digital-to-analog converters to its assigned digital-to-analog converter.
- 5. (Original) The personal computer system of claim 1 where a user configures the controller by hardware or software controls, such that the controller routes a selected analog signal to a selected one of a plurality of analog outputs.

Filing Date: November 5, 1998

Title: MULTIPLE AUDIO DACs WITH PC COMPATIBILITY

Page 3 Dkt: 450.183US1

6. The personal computer system of claim 5 where the selected analog signal is provided by one of a group consisting of the digital-to-analog converters, Compact Disc players, DVD players, microphones, TV tuners, or analog inputs.

- 7. (Original) The personal computer system of claim 1, further comprising a standard personal computer bus for transferring the digital audio signal from the digital audio source to the controller.
- 8. (Original) The personal computer system of claim 1 where the digital audio signal is transferred from the digital audio source to the controller by a direct electrical or optical connection between the two.
- 9. (Original) A method of routing digital audio to a plurality of digital-to-analog converters in a personal computer comprising the steps of:

receiving digital audio data from one of a plurality of digital audio sources; and routing the digital audio data to one of a plurality of converters based on desired converter quality.

- 10. (Original) The method of claim 9 and further comprising the steps of:
  assigning digital audio data from each source a priority;
  assigning digital audio data from each source to one of the plurality of converters;
  determining which digital audio data has the highest priority among all data
  assigned to each converter; and
- converting the digital audio data in each converter with the highest priority to analog audio.
- 11. (Original) A method of routing digital audio to a plurality of audio digital-to-analog converters in a personal computer comprising the steps of:

receiving digital audio from one of a plurality of digital audio sources;

Serial Number: 09/186,817

Filing Date: November 5, 1998

Title: MULTIPLE AUDIO DACs WITH PC COMPATIBILITY

Page 4 Dkt: 450.183US1

assigning digital audio data from each source a priority; and routing the digital audio data to one of a plurality of converters in an order determined by the assigned data priority.

12. (Original) A personal computer system comprising:

memory;

a processor;

a bus;

a plurality of digital audio converters; and

a controller configured to receive digital audio signals from multiple sources and route the digital audio signals to a selected digital-to-analog converter based on desired converter quality.

13. (Original) A method of routing digital audio signals in a personal computer comprising the steps of:

routing digital audio signals from standard digital audio sources to a standard quality digital-to-analog converter; and

routing digital audio signals from high-quality audio sources to a high-quality digital-to-analog converter.